



900W



500W / 700W




Features

- 80 PLUS® GOLD certified to deliver up to 93% efficiency.
- 13.9cm fan with thermal programmed speed controller provides silent cooling performance.
- Active PFC universal switching circuit improves Power Factor value up to 0.99, reducing AC line reactive power loss to minimum level and automatically adopting AC voltage from 100-240V.
- Over Power, Over Voltage, Over Current, Short-circuit, and Brown Out protection provide great safety to your system.
- 8P PCI-E connectors for extreme graphics cards.
- CPU 12V connector rail with >18A output to support next generation >6 cores processor structure.
- 60cm CPU connector cable facilitates installation with bottom-mounted PSU chassis.
- SATA power connectors with 3.3V rail support new generation SSD.
- Modular design provides easy cable management and system upgrade.

Extreme Efficiency: up to 93%

Extreme Safety:
diversity of
protective function

**Extreme
Compatibility:**
high 12V rails output



Extreme Quietness:
13.9cm patented design fan




		G500-MA		G700-MA		G900-MA	
AC Input	Input Voltage	100-240VAC 50-60Hz					
	Input Current	6.5 - 3A		9 - 4A		11.5 - 5A	
DC Output	+3.3V	20A	100W	24A	120W	24A	120W
	+5V	20A		24A		24A	
	+12V1	25A	492W (41A)	25A	696W (58A)	30A	900W (75A)
	+12V2	25A		25A		30A	
	+12V3	25A		25A		30A	
	+12V4	-	-	-	-	30A	
	-12V	0.5A	6W	0.5A	6W	0.5A	6W
	+5Vsb	3.0A	15W	3.0A	15W	3.0A	15W
Total Power		500W		700W		900W	

Specifications



Connectors



24 Pin Main Power

- 500W x 1
- 700W x 1
- 900W x 1



4+4 Pin CPU

- 500W x 1
- 700W x 1
- 900W x 1



8 Pin CPU

- 700W x 1
- 900W x 1



6+2 Pin PCI-E

- 500W x 2
- 700W x 4
- 900W x 6




4 Pin Peripheral

- 500W x 6
- 700W x 8
- 900W x 8



SATA


- 500W x 6
- 700W x 8
- 900W x 12



4 Pin Floppy

- 500W x 1
- 700W x 1
- 900W x 1

Modular Sockets



Modular Sockets

